



# AGIP SAGUS 60

AGIP SAGUS 60 is a dark-grey graphite grease.

## CHARACTERISTICS (TYPICAL FIGURES)

### AGIP SAGUS 60

|                             |                    |             |
|-----------------------------|--------------------|-------------|
| <b>NLGI consistency</b>     |                    | <b>0/00</b> |
| Base oil viscosity at 40 °C | mm <sup>2</sup> /s | 500         |
| Worked penetration          | dmm                | 400         |
| ASTM dropping point         | °C                 | 110         |

## PROPERTIES AND PERFORMANCE

- The structure and particle size of the graphite used in AGIP SAGUS 60 ensures perfect lubricating action under the most severe operating conditions.
- The solid film of graphite formed between the lubricated surfaces guarantees correct operation of the moving parts even when mechanical loads and thermal stresses may impair the function of the lubricating grease.
- It adheres tenaciously to metal surfaces.
- It can be dispensed by brush or by spray in centralized lubrication systems.

## APPLICATIONS

AGIP SAGUS 60 is suitable for use on exposed machine parts, even those operating at high temperature and especially for the lubrication of gears, power screws, racks, rollers, chains, wire ropes etc. It finds application principally in cement works, cable transport facilities, chemical plants etc..

## SPECIFICATIONS

AGIP SAGUS 60 meets the requirements of the following classifications:

- DIN 51826 GF 00 G-10
- ISO-L-CKG

AGIP SAGUS 60 is approved by Danieli according to Standard 0.000.001 specification